

TECHNICAL DATA


APAC - System Model No.		HSNAP25	HSNAP35	HSNAP50	HSNAP70	HSNAP80	
Nominal Capacity	kW	2.5	3.5	5.0	7.0	8.0	
Power Supply to Outdoor Unit	V-ph-Hz	220-240 - 1 - 50					
Recommended Circuit Breaker	A	16	16	20	25	25	
Connectivity	-	Wi-Fi Enabled					
Demand Response Enabling Device	-	DRED Enabled					
Rated Capacity		2.5	3.5	5.0	7.0	7.8	
Cooling	Capacity Range	1.0 ~ 3.1	1.1 ~ 3.7	1.8 ~ 5.7	2.0 ~ 8.0	2.2 ~ 8.8	
	Rated Power Input	W	590 (290 ~ 1300)	870 (290 ~ 1150)	1510 (300 ~ 2300)	2050 (400 ~ 2800)	2340 (540 ~ 3100)
	Rated Current (Range)	A	3.6 (1.3 ~ 6.5)	3.8 (1.3 ~ 5.3)	6.6 (1.4 ~ 10.3)	8.9 (1.9 ~ 13.5)	10.2 (2.6 ~ 14.9)
	AEER	W/W	4.43	4.10	3.28	3.41	3.32
	Star Rating	-	4.0	3.5	2.0	2.0	2.0
	Rated Capacity		2.5	3.5	5.0	7.0	8.0
Heating	Capacity Range	kW	1.0 ~ 3.7	1.1 ~ 4.5	1.8 ~ 6.5	2.0 ~ 8.5	2.4 ~ 9.0
	Rated Power Input	W	590 (290 ~ 1500)	850 (290 ~ 1400)	1420 (300 ~ 2450)	1950 (350 ~ 2900)	2350 (640 ~ 3650)
	Rated Current (Range)	A	3.6 (1.3 ~ 7.0)	3.7 (1.3 ~ 7.6)	6.2 (1.4 ~ 10.9)	8.5 (1.7 ~ 14.5)	10.3 (3.1 ~ 17.6)
	ACOP	W/W	4.33	4.19	3.54	3.58	3.39
	Star Rating	-	4.0	3.5	2.5	2.5	2.0
	Rated Capacity		2.5	3.5	5.0	7.0	8.0
Maximum Input Power (Cooling / Heating)	W	1300 / 1500	1150 / 1400	2300 / 2450	2800 / 2900	3100 / 3650	
Maximum Input Current (Cooling / Heating)	A	6.5 / 7.0	5.3 / 7.6	10.3 / 10.9	13.5 / 14.5	14.9 / 17.6	
Moisture Removal	L/h	0.8	1.1	2.0	2.4	2.8	
Suitable Area Coverage (up to 2.6m insulated ceiling)	m ²	13 ~ 22	18 ~ 30	26 ~ 44	37 ~ 62	41 ~ 69	

Indoor Unit Model No.		HINAP25	HINAP35	HINAP50	HINAP70	HINAP80
Air Flow (Hi / Med / Lo)	L/s	153 / 139 / 111	250 / 230 / 210	250 / 230 / 210	370 / 350 / 320	370 / 350 / 320
Sound Pressure @ 1m (Hi / Med / Lo)	dB(A)	42 / 38 / 24	45 / 41 / 32	45 / 41 / 32	52 / 47 / 30	52 / 47 / 30
Air Swing Louvers	Direction	Horizontal & Vertical				
Dimensions	Net (W x H x D)	814 x 306 x 210	972 x 310 x 225	972 x 310 x 225	1095 x 327 x 235	1095 x 327 x 235
	Packing (W x H x D)	885 x 366 x 278	1036 x 376 x 295	1036 x 376 x 295	1158 x 398 x 308	1158 x 398 x 308
	Weight Net / Gross	kg	9 / 11	12 / 15	12 / 15	15 / 18
Operating Range	Cooling	°C				
	Heating	°C				
Wireless Remote Controller	Model	52E				

Outdoor Unit Model No.		HONAP25	HONAP35	HONAP50	HONAP70	HONAP80	
Sound Power Level	dB(A)	62	62	66	70	70	
Sound Pressure Level @ 1m	dB(A)	52	52	56	60	60	
Dimensions	Dimension (W x H x D)	760x551x256	760x551x256	780x605x290	900x805x360	900x805x360	
	Packing (W x H x D)	863x600x325	863x600x325	883x653x412	1031x925x447	1031x925x447	
	Net / Gross Weight	kg	28 / 31	29 / 32	36 / 39	60 / 64	64 / 68
Refrigerant	Type	R410a					
	Charged Volume	kg	1.00	1.08	1.20	2.00	2.65
	Pipe Size: Liquid / Gas	mm	ø6.35 / ø9.52	ø6.35 / ø9.52	ø6.35 / ø12.7	ø9.52 / ø15.9	ø9.52 / ø15.9
	Maximum Pipe Length	m	15	15	15	20	20
	Maximum Vertical Separation	m	5	5	5	5	5
	Chargeless Length	m	5	5	5	5	5
Extra Charge for Lengths >5m	g/m	15	15	15	30	30	
Ambient Temperature Limits	Cooling	°C					
	Heating	°C					

Capacities tested in accordance with AS/NZS3823.3, with 5m interconnecting length. Due to our policy of continuous improvement specifications are subject to change without notice.

APAC INVERTER SPLIT SYSTEM



Low cost solution to quiet, efficient comfort

-  Sleek, modern Design
-  Wi-Fi Control
-  High Efficiency DC Inverter

 **Contact APAC**
Ph 1300 555 545
APACAIR.COM.AU

Rinnai Australia Pty Ltd
 ABN 74 005 138 769
 100 Atlantic Drive,
 Keysborough, Victoria 3173
 For further information visit
rinnai.com.au or call 1300 555 545
 AU45204

 **apac**
 by Rinnai

APAC INVERTER SPLIT SYSTEM


A World of comfort

The Apac Hi-Wall Inverter Split System technology quietly maintains steady, stable comfort control. The on-board control system continuously monitors environmental conditions to always achieve an enhanced room atmosphere.

The units produce minimum noise levels and have a built-in filter which removes dust and pollen particles from the air during operation.

Turbo mode, with its rapid cool down or warm up, helps achieve the desired room temperature in the shortest possible time.

The stylish indoor units also have vertical and horizontal louvre swing functions, which assist in achieving a perfectly distributed and comfortably even temperature throughout the room.



PRODUCT FEATURES



Sleek, modern Design



Sleep Mode



Turbo Mode



Louvre swing functions



Timer Function



Super Fine Filter



Wi-Fi Control



Auto Restart



DC Inverter



Infrared Remote Control



5 Years warranty



Wi-Fi remote control

Features include Wi-Fi Control, Turbo Mode, LCD Display, Sleep Mode and Auto Restart. Topped off with our 5 year warranty.